

ISO-9001 Registered Quality System. ISO-21469 Compliant.

## Sales, Service & Distribution Center

Newark, NJ 07105

Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605

Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

## LUBRIPLATE LITHIUM BRICK GREASE

LUBRIPLATE Lithium Brick Grease is recommended to meet the lubrication requirements of open slot or open well type bearings where the brick grease rides directly on the bearing shaft. The rotating motion of the bearing shaft wipes a film of lubricant onto the bearing surfaces keeping it properly lubricated.

LUBRIPLATE Lithium Brick Grease comes in 4-lb. Bricks (12 Bricks per Case). These Bricks are easily cut into smaller pieces to place in the bearing opening. The size of the piece should be small enough to allow freedom of movement of the block while riding on the bearing surface. From time to time, it is also a good practice to turn or rotate these pieces. Also, do not over load or over pack the bearing opening or slot.

Applications for LUBRIPLATE Lithium Brick Grease are commonly found at rock quarries and paper mills.

## **Typical Tests**

N. L. G. I.	7
Unworked Penetration @ 77°F	45 - 75
Dropping Point	325°F/165°C
Mineral Oil Base Viscosity SUS @ 100°F cSt @ 40°C	450 - 550 100
Viscosity Index	80
Soap	Lithium 12-Hydroxy
% of Thickener	12 - 18
Color	Amber
Texture	Smooth
Packaging Available	Part No.
48 lb. Carton (12 - 4-lb. Bricks)	L0132-038

Printed in USA Revised 10/14/11