



SAFETY DATA SHEET

Chain and Cable

According to WHMIS 2015, in compliance with the Hazardous Product Act (HPA, as amended) and the requirements of the Hazardous Product Regulations (HPR)

1. Identification

Product identifier

Product name Chain and Cable

Product number L0135-063, L0135-063C

Recommended use of the chemical and restrictions on use

Restriction on use Lubricant for chains, wires and cables.

Uses advised against No specific uses advised against are identified.

Details of the supplier of the safety data sheet

Supplier Summit Agencies Ltd.
440-10816 Macleod Trail S.
Calgary, Alberta T2J 5N8
403-236-8655

Mechanical Sales Co.
431 Huronia Road
Unit 4
Barrie, Ontario L4N 9B3
800-263-7226

Manufacturer Lubriplate Lubricants Co.
Corporate Headquarters
129 Lockwood Street
Newark, NJ 07105

Midwest Office & Plant
1500 Oakdale Ave.
Toledo, OH 43605
419-691-2491
419-693-3806

Emergency telephone number

Emergency telephone Chem-Tel: 1-800-255-3924 (US & Canada only)
01-813-248-0585 (Outside US & Canada)

2. Hazard identification

Classification of the substance or mixture

Physical hazards Flam. Aerosol 2 - H223 Press. Gas, Compressed - H280

Health hazards Skin Sens. 1 - H317 Asp. Tox. 1 - H304

Environmental hazards Not Classified

Label elements

Chain and Cable

Pictogram



Signal word

Danger

Hazard statements

H223 Flammable aerosol.
 H280 Contains gas under pressure; may explode if heated.
 H304 May be fatal if swallowed and enters airways.
 H317 May cause an allergic skin reaction.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P261 Avoid breathing spray.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P321 Specific treatment (see medical advice on this label).
 P331 Do NOT induce vomiting.
 P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P405 Store locked up.
 P410+P403 Protect from sunlight. Store in a well-ventilated place.
 P412 Do not expose to temperatures exceeding 50°C/122°F.
 P501 Dispose of contents/ container in accordance with national regulations.

Contains

Distillates (petroleum), hydrotreated light, Calcium Sulfonate

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients

Mixtures

Distillates (petroleum), hydrotreated light CAS number: 64742-47-8	60-100%
Classification Asp. Tox. 1 - H304	
Distillates (petroleum), hydrotreated heavy naphthenic CAS number: 64742-52-5	5-10%
Classification Not Classified	

Chain and Cable

Carbon dioxide CAS number: 124-38-9	1-5%
Classification Simple Asphyxiants - Category 1	
2-butoxyethanol CAS number: 111-76-2	1-5%
Classification Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319	
Pentene, 2,4,4-trimethyl-, sulfurized CAS number: 68515-88-8	<1%
Classification Skin Sens. 1B - H317	
Calcium Sulfonate CAS number: 61789-86-4	<1%
Classification Skin Sens. 1 - H317	
White mineral oil (petroleum) CAS number: 8042-47-5	<1%
Classification Not Classified	

The full text for all hazard statements is displayed in Section 16.

4. First-aid measures

Description of first aid measures

General information	Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Loosen tight clothing such as collar, tie or belt. Get medical attention if symptoms are severe or persist.
Ingestion	Rinse mouth thoroughly with water. Get medical advice/attention if you feel unwell. Do not induce vomiting unless under the direction of medical personnel.
Skin contact	Rinse with water.
Eye contact	Remove any contact lenses and open eyelids wide apart. Rinse with water. Get medical attention if any discomfort continues.

Chain and Cable

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue.

Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation Spray/mists may cause respiratory tract irritation.

Ingestion Due to the physical nature of this product, it is unlikely that ingestion will occur. Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

Skin contact Repeated exposure may cause skin dryness or cracking.

Eye contact May be slightly irritating to eyes. May cause discomfort.

Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

Chain and Cable

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the hazardous product

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. Bursting aerosol containers may be propelled from a fire at high speed. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant.

Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing that provides a basic level of protection during chemical incidents is defined by the Canada Occupational Health and Safety Regulations, by provincial guidelines on occupational health and safety or by NFPA standards if applicable.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be taken without appropriate training or involving any personal risk. Do not touch or walk into spilled material. Evacuate area. Risk of explosion.

Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground.

Methods and material for containment and cleaning up

Methods for cleaning up Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Under normal conditions of handling and storage, spillages from aerosol containers are unlikely. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. Small Spillages: Wipe up with an absorbent cloth and dispose of waste safely. Large Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.

Reference to other sections

Chain and Cable

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

Chain and Cable

7. Handling and storage

Precautions for safe handling

Usage precautions

Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Avoid exposing aerosol containers to high temperatures or direct sunlight. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin. Avoid contact with eyes. Avoid inhalation of vapours and spray/mists.

Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse.

Conditions for safe storage, including any incompatibilities

Storage precautions

Store away from incompatible materials (see Section 10). Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Protect from sunlight. Do not store near heat sources or expose to high temperatures. Do not expose to temperatures exceeding 50°C/122°F.

Storage class

Chemical storage.

Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

Distillates (petroleum), hydrotreated heavy naphthenic

Mineral oil, excluding metal working fluids (pure, highly and severely refined)
ACGIH

Carbon dioxide

Long-term exposure limit (8-hour TWA): ACGIH 5000 ppm 9000 mg/m³
Short-term exposure limit (15-minute): ACGIH 30000 ppm 54000 mg/m³

2-butoxyethanol

Long-term exposure limit (8-hour TWA): ACGIH 20 ppm 97 mg/m³
A3

White mineral oil (petroleum)

Mineral oil, excluding metal working fluids (pure, highly and severely refined)
ACGIH = American Conference of Governmental Industrial Hygienists.
A3 = Confirmed Animal Carcinogen with Unknown Relevance to Humans.

Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Observe any occupational exposure limits for the product or ingredients.

Chain and Cable

Eye/face protection	Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.
Hand protection	No specific hand protection recommended.
Other skin and body protection	Wear appropriate clothing to prevent repeated or prolonged skin contact.
Hygiene measures	Wash after use and before eating, smoking and using the toilet. Do not eat, drink or smoke when using this product.
Respiratory protection	Ensure all respiratory protective equipment is suitable for its intended use and is NIOSH approved. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work. Full face mask respirators with replaceable filter cartridges should comply with the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work. Half mask and quarter mask respirators with replaceable filter cartridges should comply with the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work.
Environmental exposure controls	Keep container tightly sealed when not in use.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Off-white.
Odour	Not available.
Odour threshold	Not available.
pH	Not available.
Melting point	Not available.
Initial boiling point and range	Not available.
Flash point	Not applicable.
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	0.93 (without propellant)
Solubility(ies)	Insoluble in water.
Partition coefficient	Not available.
Auto-ignition temperature	Not available.
Decomposition Temperature	Not available.

Chain and Cable

Viscosity	Not available.
Explosive properties	Not considered to be explosive.
Oxidising properties	Does not meet the criteria for classification as oxidizing.

10. Stability and reactivity

Reactivity	See the other subsections of this section for further details.
Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
Possibility of hazardous reactions	No potentially hazardous reactions known.
Conditions to avoid	Avoid heat, flames and other sources of ignition.
Materials to avoid	Oxidizing materials. Chlorine.
Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀)	Based on available data the classification criteria are not met.
ATE oral (mg/kg)	27,956.7

Acute toxicity - dermal

Notes (dermal LD₅₀)	Based on available data the classification criteria are not met.
ATE dermal (mg/kg)	61,504.74

Acute toxicity - inhalation

Notes (inhalation LC₅₀)	Based on available data the classification criteria are not met.
ATE inhalation (vapours mg/l)	615.05

Skin corrosion/irritation

Animal data	Based on available data the classification criteria are not met.
--------------------	--

Serious eye damage/irritation

Serious eye damage/irritation	Based on available data the classification criteria are not met.
--------------------------------------	--

Respiratory sensitization

Respiratory sensitization	Based on available data the classification criteria are not met.
----------------------------------	--

Skin sensitization

Skin sensitization	May cause an allergic skin reaction.
---------------------------	--------------------------------------

Germ cell mutagenicity

Genotoxicity - in vitro	Based on available data the classification criteria are not met.
--------------------------------	--

Carcinogenicity

Carcinogenicity	Based on available data the classification criteria are not met.
------------------------	--

Chain and Cable

IARC carcinogenicity Contains a substance which may be potentially carcinogenic. IARC Group 3 Not classifiable as to its carcinogenicity to humans.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity - development Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Asp. Tox. 1 - H304 May be fatal if swallowed and enters airways. Pneumonia may be the result if vomited material containing solvents reaches the lungs.

General information The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation Spray/mists may cause respiratory tract irritation.

Ingestion Due to the physical nature of this product, it is unlikely that ingestion will occur. Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

Skin contact Repeated exposure may cause skin dryness or cracking.

Eye contact May be slightly irritating to eyes. May cause discomfort.

Route of exposure Ingestion Inhalation Skin and/or eye contact

Target organs No specific target organs known.

12. Ecological Information

Ecotoxicity Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.

Toxicity Based on available data the classification criteria are not met.

Persistence and degradability

Persistence and degradability The degradability of the product is not known.

Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not available.

Mobility in soil

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

Other adverse effects

Other adverse effects None known.

13. Disposal considerations

Chain and Cable

Waste treatment methods

General information

The generation of waste should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

Disposal methods

Do not empty into drains. Empty containers must not be punctured or incinerated because of the risk of an explosion. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labeled with their contents.

14. Transport information

General

For limited quantity packaging/limited load information, consult the relevant modal documentation using the data shown in this section.

UN number

UN No. (TDG)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950
UN No. (DOT)	UN1950

UN proper shipping name

Proper shipping name (TDG)	AEROSOLS
Proper shipping name (IMDG)	AEROSOLS
Proper shipping name (ICAO)	AEROSOLS
Proper shipping name (DOT)	AEROSOLS

Transport hazard class(es)

DOT class	2.2
DOT hazard label	2.2
TDG class	2.2
TDG label(s)	2.2
IMDG class	2.2
ICAO class/division	2.2

Transport labels



DOT transport label



Chain and Cable

Packing group

TDG packing group	None
IMDG packing group	None
ICAO packing group	None
DOT packing group	None

Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

Special precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

EmS F-D, S-U

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

Inventories

Canada – DSL/NDSL

The following ingredients are listed or exempt:

Distillates (petroleum), hydrotreated light

Carbon dioxide

Distillates (petroleum), hydrotreated heavy naphthenic

2-butoxyethanol

Calcium Sulfonate

Methacrylate copolymer

White mineral oil (petroleum)

Alkyl methacrylate

Naphthenic acids, zinc salts

Distillates (petroleum), hydrotreated middle

Zinc neodecanoate

Pentene, 2,4,4-trimethyl-, sulfurized

Petroleum oil

Polyisobutylene

Sorbitan monooleate, ethoxylated

16. Other information

Classification abbreviations and acronyms	Aerosol = Aerosol Press. Gas (Diss.) = Gas under pressure: Dissolved gas
Training advice	Only trained personnel should use this material.
Revision date	2018-06-29

Chain and Cable

SDS number 5194

Hazard statements in full

H223 Flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
May displace oxygen and cause rapid suffocation.

End of SDS

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.